

## Discover the Essex Advantage

### UV PANEL COATING TECHNOLOGY

Super Seal is a universal sealer that allows end users to apply their own finish. Our custom formula increases adhesion and reduces finishing room bottlenecks.

We seal and sand your panels saving you material costs, labor and time. It is compatible with many topcoats.

## Essex Super Seal performance specifications



### IDEAL APPLICATIONS

- CUSTOM FINISHING
- FIELD FINISHING
- OPAQUE COLOR FINISHES
- TINTED TOPCOATS

### VENEERS & SUBSTRATES

All types, cores and raw faces

### SEALER THICKNESS

1 – 1.5 mil

\*will vary with wood species

### EMISSIONS

No VOCs, No HAPs, No Formaldehyde

### TOPCOAT COMPATIBILITY

Conversion Varnish  
Acid Cure Catalyzed Lacquer  
Pre-catalyzed lacquered  
Two-component Urethane

### LEED CREDITS

IEQ Low Emitting Materials – Adhesives & Sealants  
MR Regional Materials

\*Depends on project and LEED rating system used

### SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT (SCAQMD)

Meets SCAQMD Rule 1113, Architectural Coatings  
Meets SCAQMD Rule 1168, Adhesives & Sealants  
Meets “Superclean” requirements (<5% by Wt. VOC)

### STANDARDS

Our products meet various states, national and international standards. Contact us if you are looking for a specific requirement or need more technical information for your project.

### OUR PHILOSOPHY

We take special pride in the distinctive quality and appearance of our finishes. We believe that service and quality are the underpinnings of great business relationships and great products.

### MORE QUESTIONS

Call us directly to discuss your project. We are happy to answer your questions and discuss how one of our products can assist you.

ESSEX SUPER SEAL

SUPER SEAL

+

PRE-CAT LACQUERED TOPCOAT